

LCD&LCM
SPECIFICATION
液晶显示屏产品使用说明书

MODULE NO.

160160C027

160x160 图形点阵

COG 工艺

4 线 SPI 或 8 位并口通讯

支架背光带安装固定孔

Designed	Checked	Approved

申 明

本产品属我司公模产品，我司保留对此文件及产品进行修改升级的权利且不另行通知，请于向我公司提出订单前，自行确定所使用的相关技术文件及产品规格为最新版本。规格书中之相关内容相信是正确的，但并不保证绝无错误，欢迎提出宝贵建议以便更加完善资料。

若因贵公司使用我公司的文件或产品，而涉及到第三方之专利或版权等相关产权的应用时，则由贵公司负责取得相关授权，我公司不承担由此引起的相关责任。

Revision history 修改记录

revision	date	description	remark
A00	2016-10-12	First release	

Content/目录

- 1. Feature/显示特性**
- 2. Mechanical specifications/外形尺寸说明**
- 3. Block diagram & power supply/电路原理图**
- 4. Pin description/PIN 脚描述**
- 5. Absolute maximum rating/限定参数**
- 6. Electrical characteristics/电气特性**
- 7. Backlight characteristics/背光特性**
- 8. Electrical-optical characteristics/光学特性**
- 9. Control and display commands/指令描述**
- 10. DDRAM 映射表**
- 11. Inspection standards/检验标准**
- 12. Handling precautions/注意事项**

1. Feature/显示特性


Display resolution/点阵数	: 160(w)*160(h)
Display mode/显示模式	: FSTN ,Positive, Transflective (or Negative,Transmissive)
Driving method/驱动方式	: 1/160 Duty , 1/10 Bias
Viewing direction/视角	: 6:00 o'clock
Backlight/背光	: LED , White(or Other)
Built-in controller/控制器	: UC1698
Operation temp/工作温度	: -20℃~+70℃ (or -40℃~+70℃)
Storage temp/储存温度	: -30℃~+80℃ (or -40℃~+80℃)

2. Mechanical Specifications/外形尺寸说明


2.1 尺寸描述

Dimensional outline (W*H*T)/外形尺寸	: 79.65mm*72.6mm*4.8mm
Viewing area (W*H)/视域尺寸	: 60.0mm*60.0mm
Active area(W*H)/显示尺寸	: 80.38mm*47.18mm
Dot pitch (W*H)/点距	: 0.34mm*0.34mm
Dot size (W*H)/点大小	: 0.32mm*0.32mm
Weigh/重量 t	: Approx

2.2 Outline Dimension 外形尺寸图



3. Block Diagram & Power supply/电路原理图



4. Pin description/PIN 脚描述

Pin No.	Pin Name	Function
1	VLCD	Connect capacitors Ground 倍压输出
2	VS+	接无极性电容
3	VS-	
4	CB0-	
5	CB1-	
6	CB1+	
7	CB0+	
8	VDD	Power Supply. 3.3V 电源
9	VSS	GND. 0V 地
10	TST4	测试脚，悬空即可
11	BM0	BM0=1是6800时序，BM0=0是8080时序，4线SPI串口通讯时接低（VSS）
12	CS0	Chip select input pin. 片选
13	CD	Register select input, H: data; L: command 选择写入的是指令或数据
14	WR1	8080时序时，WR0=写入，WR1=读； 6800时序时，WR0=读/写，WR1=EN使能； 4线SPI串口通讯时，WR0和WR1均接低（VSS）
15	WR0	
16	RST	Reset signal (Low effective) 复位
17 · · · 24	D0 · · · D7	8位并口通讯时为数据总线（DATA BUS） 4线SPI串口通讯时，D0为SCK(时钟)，D1~D7为空（或接VSS）
25	D8	
26	D13	并口通讯时接高（VDD），4线SPI串口通讯时接低（VSS）
27	D15	并口通讯时接高（VSS），4线SPI串口通讯时接低（VDD）
背光	A+	LED正极，工作电压3.0V，工作电流50mA~60mA
	K-	LED负极，0V

5. Absolute Maximum Ratings/限定参数

Items	Symbol	MIN.	MAX.	Unit	Condition
Supply Voltage/供电电压	VDD	-0.3	+3.3	V	Vss = 0V
	Vlcd	-0.3	+16.5	V	Vss = 0V
Input Voltage/输入电压	VIN	-0.3	VDD+0.3	V	Vss = 0V
LED forward current/背光电流	If	0	50	mA	---
Operating Temp./工作温度	TOP	-20	+70	℃	---
Storage Temp./储存温度	Tst	-30	+80	℃	---

6. Electrical Characteristics/电气特性

6.1 Typical Electrical Characteristics

($V_{SS} = 0V$, $V_{DD} = 3.3V \pm 10\%$, $T_{op} = 25^{\circ}C$)

ABSOLUTE MAXIMUM RATINGS

In accordance with IEC134, note 1 and 2.

Symbol	Parameter	Min.	Max.	Unit
V_{DD}	Logic Supply voltage	-0.3	+4.0	V
V_{DD2}	LCD Generator Supply voltage	-0.3	+4.0	V
V_{DD3}	Analog Circuit Supply voltage	-0.3	+4.0	V
$V_{DD2/3}-V_{DD}$	Voltage difference between V_{DD} and $V_{DD2/3}$	—	1.6	V
V_{LCD}	LCD Generated voltage ($-30^{\circ}C \sim +80^{\circ}C$)	-0.3	+19.8	V
V_{IN}	Digital input signal	-0.4	$V_{DD} + 0.5$	V
T_{OPR}	Operating temperature range	-30	+85	$^{\circ}C$
T_{STR}	Storage temperature	-55	+125	$^{\circ}C$

Notes

- V_{DD} is based on $V_{SS} = 0V$
- Stress beyond ranges listed above may cause permanent damages to the device.

SPECIFICATIONS

DC CHARACTERISTICS

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{DD}	Supply for digital circuit		1.65		3.3	V
$V_{DD2/3}$	Supply for bias & pump		2.7		3.3	V
V_{LCD}	Charge pump output	$V_{DD2/3} = 2.8V$, $25^{\circ}C$		15.2	18	V
V_D	LCD data voltage	$V_{DD2/3} = 2.8V$, $25^{\circ}C$	1.09		1.95	V
V_{IL}	Input logic LOW				$0.2V_{DD}$	V
V_{IH}	Input logic HIGH		$0.8V_{DD}$			V
V_{OL}	Output logic LOW				$0.2V_{DD}$	V
V_{OH}	Output logic HIGH		$0.8V_{DD}$			V
I_{IL}	Input leakage current				1.5	μA
I_{SB}	Standby current	$V_{DD} = V_{DD2/3} = 3.3V$, Temp = $85^{\circ}C$			50	μA
C_{IN}	Input capacitance			5	10	PF
C_{OUT}	Output capacitance			5	10	PF
$R_{ON(SEG)}$	SEG output impedance	$V_{LCD} = 15V$		750	1100	Ω
$R_{ON(COM)}$	COM output impedance	$V_{LCD} = 15V$		750	1100	Ω
f_{LINE}	Average line rate	LC[4:3] = 10b, $25^{\circ}C$	-10%	37.0	+10%	Klps

POWER CONSUMPTION

$V_{DD} = 2.7V$,
 $V_{LCD} = 16.5V$,
 Mux Rate = 160,
 $C_B = 2.2\mu F$,
 N-line inversion = 31 lines

Bias Ratio = 12,
 Line Rate = 10b,
 Bus mode = 6800,
 Temperature = $25^{\circ}C$,
 Color Mode = 64K color mode,

PM = 64,
 Panel Loading (PC[1:0]) = 0b,
 $C_L = 330nF$,
 MTP=00 H,
 All HV outputs are open circuit.

Display Pattern	Conditions	Typ. (μA)	Max. (μA)
All-Pixel-OFF	Bus = idle	1764	(TBD)
2-pixel checker	Bus = idle	2468	(TBD)
None	Reset (stand-by current)	<1	5

6.2 Timing Specifications

6.2.1. 8080 Mode System Bus Timing




FIGURE 14: Parallel Bus Timing Characteristics (for 8080 MCU)

($2.5V \leq V_{DD} < 3.3V$, $T_a = -30$ to $+85^\circ C$)

Symbol	Signal	Description	Condition	Min.	Max.	Units
t_{AS80}	CD	Address setup time		0	—	nS
t_{AH80}	CD	Address hold time		0	—	nS
t_{CY80}		System cycle time			—	nS
		16-bit bus (read)		170	—	nS
		16-bit bus (write)		130	—	nS
		8-bit bus (read)		100	—	nS
		8-bit bus (write)		80	—	nS
t_{PWR80}	WR1	Pulse width 16-bit (read)		85	—	nS
		8-bit		50	—	nS
t_{PWW80}	WR0	Pulse width 16-bit (write)		65	—	nS
		8-bit		40	—	nS
t_{HPW80}	WR0, WR1	High pulse width			—	nS
		16-bit bus (read)		85	—	nS
		16-bit bus (write)		65	—	nS
		8-bit bus (read)		50	—	nS
		8-bit bus (write)		40	—	nS
t_{DS80}	D0~D15	Data setup time		30	—	nS
t_{DH80}	D0~D15	Data hold time		0	—	nS
t_{ACC80}		Read access time	$C_L = 100pF$	—	60	nS
t_{OD80}		Output disable time		15	30	nS
t_{CSSA80}	CS1/CS0	Chip select setup time		5	—	nS
t_{CSH80}	CS1/CS0	Chip select hold time		5	—	nS

6.2.2. 6800 Mode System Bus Timing




FIGURE 15: Parallel Bus Timing Characteristics (for 6800 MCU)

(2.5V ≤ V_{DD} < 3.3V, T_a = –30 to +85°C)

Symbol	Signal	Description	Condition	Min.	Max.	Units
t _{AS68}	CD	Address setup time		0	–	nS
t _{AH68}		Address hold time		0	–	nS
t _{CY68}		System cycle time			–	nS
		16-bit bus (read)		170		
		8-bit bus (write)		130		
		16-bit bus (read)		100		
		8-bit bus (write)		80		
t _{PWR68}	WR1	Pulse width 16-bit (read)		85	–	nS
		8-bit		50		
t _{PWW68}		Pulse width 16-bit (write)		65	–	nS
		8-bit		40		
t _{LPW68}		Low pulse width			–	nS
		16-bit bus (read)		85		
		8-bit bus (write)		65		
		16-bit bus (read)		50		
		8-bit bus (write)		40		
t _{DS68}	D0~D7	Data setup time		30	–	nS
t _{DH68}		Data hold time		0	–	nS
t _{ACC68}		Read access time	C _L = 100pF	–	60	nS
t _{OD68}		Output disable time		15	30	nS
t _{CSSA68}	CS1/CS0	Chip select setup time		5		nS
t _{CSH68}				5		nS

6.2.3 . 4-Wires SPI Serial Bus Timing




FIGURE 16: Serial Bus Timing Characteristics (for S8/S8uc)

(2.5V ≤ V_{DD} < 3.3V, T_a = –30 to +85°C)

Symbol	Signal	Description	Condition	Min.	Max.	Units
t _{ASS8}	CD	Address setup time		0	–	nS
t _{AHS8}		Address hold time		0	–	nS
t _{CYS8}	SCK	System cycle time		40	–	nS
t _{LPWS8}		Low pulse width		20	–	nS
t _{HPWS8}		High pulse width		20	–	nS
t _{DSS8}	SDA	Data setup time		15	–	nS
t _{DHS8}		Data hold time		0	–	nS
t _{CSSAS8}	CS1/CS0	Chip select setup time		5		nS
t _{CSHS8}				5		nS

Reset timing




FIGURE 17: Reset Characteristics

(1.65V ≤ V_{DD} < 3.3V, T_a = –30 to +85°C)

Symbol	Signal	Description	Condition	Min.	Max.	Units
t _{RW}	RST	Reset low pulse width		3	–	μS
t _{RD}	RST, WR	Reset to WR pulse delay		10	–	mS


7. Backlight Characteristics/背光特性

Items	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Forward Voltage/电压	Vf	2.8	3.0	3.1	V	If=50mA
Reverse current/电流	Ir	---	50	60	mA	Vr=3V
Peak wave length/波长	λ	---	---	---	nM	If=30mA
Luminance/亮度	Lv	---	---	---	Cd/m ²	If=30mA
Color /颜色	White (白色, 或者其他色)					


8. Electrical-Optical Characteristics/光学特性

Items	Symbol	Condition	MIN.	TYP.	MAX.	Unit	NOTE
Response time/反应时间	Tr	Ta= 25℃	---	250	---	ms	2
	Tf		---	400	---		
Contrast ratio/对比度	Cr	Ta= 25℃	---	--	---		3
Viewing angle range/视角范围	θ	Cr $\geq$ 2	-40	---	40	degree	


Note 1. Definition of response time



Note2 . Definition of Contrast Ratio‘Cr’



Note 3. Definition of Viewing Angle Range ‘ θ ’



9. Control and display commands/指令描述

COMMAND TABLE

The following is a list of host commands supported by UC1698u

C/D: 0: Control, 1: Data
W/R: 0: Write Cycle, 1: Read Cycle
#: Useful Data bits - : Don't Care

	Command	C/D	W/R	D7	D6	D5	D4	D3	D2	D1	D0	Action		Default	
1	Write Data Byte	1	0	#	#	#	#	#	#	#	#	Write 1 byte		N/A	
2	Read Data Byte	1	1	#	#	#	#	#	#	#	#	Read 1 byte		N/A	
3	Get Status & PM	0	1	GE	MX	MY	WA	DE	WS	MD	MS	Get {Status, Ver, PMO, Product Code, PID, MID}		N/A	
				Ver	PMO[6:0]										
				Product Code (8h)			PID[1:0]		MID[1:0]						
4	Set Column Address LSB	0	0	0	0	0	0	#	#	#	#	Set CA[3:0]		0	
	Set Column Address MSB	0	0	0	0	0	1	0	#	#	#	Set CA[6:4]		0	
5	Set Temp. Compensation	0	0	0	0	1	0	0	1	#	#	Set TC[1:0]		0	
6	Set Power Control	0	0	0	0	1	0	1	0	#	#	Set PC[1:0]		10b	
7	Set Adv. Program Control (double-byte command)	0	0	0	0	1	1	0	0	0	R	Set APC[R][7:0], R = 0 or 1		N/A	
		0	0	#	#	#	#	#	#	#	#				
8	Set Scroll Line LSB	0	0	0	1	0	0	#	#	#	#	Set SL[3:0]		0	
	Set Scroll Line MSB	0	0	0	1	0	1	#	#	#	#	Set SL[7:4]		0	
9	Set Row Address LSB	0	0	0	1	1	0	#	#	#	#	Set RA[3:0]		0	
	Set Row Address MSB	0	0	0	1	1	1	#	#	#	#	Set RA[7:4]		0	
10	Set V _{BIAS} Potentiometer (double-byte command)	0	0	1	0	0	0	0	0	0	1	Set PM[7:0]		40H	
		0	0	#	#	#	#	#	#	#	#				
11	Set Partial Display Control	0	0	1	0	0	0	0	1	0	#	Set LC[8]		0	
12	Set RAM Address Control	0	0	1	0	0	0	1	#	#	#	Set AC[2:0]		001b	
13	Set Fixed Lines	0	0	1	0	0	1	0	0	0	0	Set {FLT,FLB}		0	
		0	0	#	#	#	#	#	#	#	#				
14	Set Line Rate	0	0	1	0	1	0	0	0	#	#	Set LC[4:3]		10b	
15	Set All-Pixel-ON	0	0	1	0	1	0	0	1	0	#	Set DC[1]		0	
16	Set Inverse Display	0	0	1	0	1	0	0	1	1	#	Set DC[0]		0	
17	Set Display Enable	0	0	1	0	1	0	1	#	#	#	Set DC[4:2]		110b	
18	Set LCD Mapping Control	0	0	1	1	0	0	0	#	#	#	Set LC[2:0]		0	
19	Set N-Line Inversion	0	0	1 -	1 -	0 -	0 #	1 #	0 #	0 #	0 #	Set NIV[4:0]		1DH	
20	Set Color Pattern	0	0	1	1	0	1	0	0	0	#	Set LC[5]		0 (BGR)	
21	Set Color Mode	0	0	1	1	0	1	0	1	#	#	Set LC[7:6]		10b	
22	Set COM Scan Function	0	0	1	1	0	1	1	#	#	#	Set CSF[2:0]		000b	
23	System Reset	0	0	1	1	1	0	0	0	1	0	System Reset		N/A	
24	NOP	0	0	1	1	1	0	0	0	1	1	No operation		N/A	
25	Set Test Control (double-byte command)	0	0	1	1	1	0	0	1	TT		For testing only. Do not use.		N/A	
		0	0	#	#	#	#	#	#	#	#				
26	Set LCD Bias Ratio	0	0	1	1	1	0	1	0	#	#	Set BR[1:0]		11b: 12	
27	Set COM End	0	0	1	1	1	1	0	0	0	1	Set CEN[6:0]		159	
		0	0	-	#	#	#	#	#	#	#				
28	Set Partial Display Start	0	0	1	1	1	1	0	0	1	0	Set DST[6:0]		0	
		0	0	-	#	#	#	#	#	#	#				
29	Set Partial Display End	0	0	1	1	1	1	0	0	1	1	Set DEN[6:0]		159	
		0	0	-	#	#	#	#	#	#	#				
30	Set Window Program Starting Column Address	0	0	1	1	1	1	0	1	0	0	Shared with MTP commands		Set WPC0	0
		0	0	-	#	#	#	#	#	#	#				
31	Set Window Program Starting Row Address	0	0	1	1	1	1	0	1	0	1			Set WPP0	0
		0	0	#	#	#	#	#	#	#	#				
32	Set Window Program Ending Column Address	0	0	1	1	1	1	0	1	1	0			Set WPC1	127
		0	0	-	#	#	#	#	#	#	#				
33	Set Window Program Ending Row Address	0	0	1	1	1	1	0	1	1	1			Set WPP1	159
		0	0	#	#	#	#	#	#	#	#				
34	Window Program Mode	0	0	1	1	1	1	1	0	0	#	Set AC[3]		0: Inside	
35	Set MTP Operation control	0	0	1	0	1	1	1	0	0	0	Set MTPC[4:0]		10H	
		0	0	-	-	-	#	#	#	#	#				

	Command	C/D	W/R	D7	D6	D5	D4	D3	D2	D1	D0	Action	Default
36	Set MTP Write Mask	0 0 0	0 0 0	1 - -	0 # -	1 # -	1 # -	1 # -	0 # -	0 # #	1 # #	Set MTPM[6:0] MTPM1[1:0]	0
37	Set V_{MTP1} Potentiometer	0 0	0 0	1 #	1 #	1 #	1 #	0 #	1 #	0 #	0 #	Shared with Window Program commands	Set MTP1 N/A
38	Set V_{MTP2} Potentiometer	0 0	0 0	1 #	1 #	1 #	1 #	0 #	1 #	0 #	1 #		Set MTP2 N/A
39	Set MTP Write Timer	0 0	0 0	1 #	1 #	1 #	1 #	0 #	1 #	1 #	0 #		Set MTP3 N/A
40	Set MTP Read Timer	0 0	0 0	1 #	1 #	1 #	1 #	0 #	1 #	1 #	1 #		Set MTP4 N/A

NOTE:

- All other bit patterns other than commands listed above may result in undefined behavior.
- The interpretation of commands (36)~(40) depends on the setting of register MTPC[3].
 - Commands (37)~(40) are shared with commands (30)~(33). These two sets of commands share exactly the same code and control registers. When MTPC[3]=0, they are interpreted as Window Program commands and registers. When MTPC[3]=1, they function as MTP Control commands and registers.
- After MTP ERASE or PROGRAM operation, before resuming normal operation, please always
 - Remove TST4 power source.
 - Do a full V_{DD} ON-OFF-ON cycle.
- Under 16-bit bus mode and CD=0, D[15:8] is ignored and only D[7:0] is used. As a result, the bus cycles for commands under 16-bit bus and 8-bit bus are the same, and double-byte commands still need two bus cycles under 16-bit bus mode.

Example:

8-bit bus mode:

Set PL[1:0] = 2'b11 : D[7:0] = 0010 1011Set PM[7:0] = 8'h8b : 1st D[7:0] = 1000 00012nd D[7:0] = 1000 1011

16-bit bus mode:

Set PL[1:0] = 2'b11: D[15:0] = 0000 0000 0010 1011Set PM[7:0] = 8'h8b: 1st D[15:0] = 0000 0000 1000 00012nd D[15:0] = 0000 0000 1000 1011

10. DDRAM 映射表

DISPLAY DATA RAM

DATA ORGANIZATION

The input display data (depend on color mode) are stored to a dual port static RAM (RAM, for Display Data RAM) organized as 160x128X16.

After setting CA and RA, the subsequent data write cycles will store the data for the specified pixel to the proper memory location.

Please refer to the map in the following page between the relation of COM, SEG, SRAM, and various memory control registers.

DISPLAY DATA RAM ACCESS

The Display RAM is a special purpose dual port RAM which allows asynchronous access to both its column and row data. Thus, RAM can be independently accessed both for Host Interface and for display operations.

DISPLAY DATA RAM ADDRESSING

A Host Interface (HI) memory access operation starts with specifying Row Address (RA) and Column Address (CA) by issuing *Set Row Address* and *Set Column Address* commands.

If wrap-around (WA, AC[0]) is OFF (0), CA will stop incrementing after reaching the end of row

ROW MAPPING

COM electrode scanning orders are not affected by Start Line (SL), Fixed Line (FLT & FTB) or Mirror Y (MY, LC[3]). Visually, register SL having a non-zero value is equivalent to scrolling the LCD display up or down (depends on MY) by SL rows.

RAM ADDRESS GENERATION

The mapping of the data stored in the display SRAM and the scanning COM electrodes can be obtained by combining the fixed COM scanning sequence and the following RAM address generation formula.

When FL=0, during the display operation, the RAM line address generation can be mathematically represented as following:

For the 1st line period of each field

$$Line = SL$$

Otherwise

$$Line = \text{Mod}(Line+1, 160)$$

Where Mod is the modular operator, and *Line* is the bit slice line address of RAM to be outputted to SEG drivers. Line 0 corresponds to the first bit-slice of data in RAM.


WINDOW PROGRAM

Window program is designed for data write in a specified window range of SRAM address. The procedure should start with window boundary registers setting ($WPP0$, $WPP1$, $WPC0$ and $WPC1$) and $AC[3]$ setting for inside/outside window mode. When $AC[3]$ is set to '0' (default value), data can be written to SRAM within the window address range which is specified by ($WPP0$, $WPC0$) and ($WPP1$, $WPC1$). When $AC[3]$ is set to '1', data will be written to whole SRAM excluding the specified window area.


The data write direction will be determined by $AC[2:0]$ and MX settings. When $AC[0]=1$, the data write can be consecutive within the range of the specified window. $AC[1]$ will control the data write in either column or row direction. $AC[2]$ will result the data write starting either from row $WPP0$ or $WPP1$. MX is for the initial column address either from $WPC0$ to $WPC1$ or from ($MC-WPC0$ to $MC-WPC1$).

Example1 ($AC[2:0] = 001$) :


$AC[3]=0$ $MX=0$

**Example 2** ($AC[2:0] = 111$) :


$AC[3] = 0$ $MX = 0$

**Example1-1 :**

$AC[3]=1$ $MX=0$

**Example 2-1 :**

$AC[3] = 1$ $MX = 0$



Row Address	RAM											MY=0		MY=1	
												SL=0	SL=16	SL=0	SL=16
00H												COM1	COM17	COM160	COM16
01H												COM2	COM18	COM159	COM15
02H												COM3	COM19	COM158	COM14
03H												COM4	COM20	COM157	COM13
04H												COM5	COM21	COM156	COM12
05H												COM6	COM22	COM155	COM11
06H												COM7	COM23	COM154	COM10
07H												COM8	COM24	COM153	COM9
08H												COM9	COM25	COM152	COM8
09H												COM10	COM26	COM151	COM7
0AH												COM11	COM27	COM150	COM6
0BH												COM12	COM28	COM149	COM5
0CH												COM13	COM29	COM148	COM4
0DH												COM14	COM30	COM147	COM3
0EH												COM15	COM31	COM146	COM2
0FH												COM16	COM32	COM145	COM1
10H												COM17	COM33	COM144	COM160
11H												COM18	COM34	COM143	COM159
12H												COM19	COM35	COM142	COM158
13H												COM20	COM36	COM141	COM157
14H												COM21	COM37	COM140	COM156
15H												COM22	COM38	COM139	COM155
16H												COM23	COM39	COM138	COM154
17H												COM24	COM40	COM137	COM153
18H												COM25	COM41	COM136	COM152
19H												COM26	COM42	COM135	COM151
1AH												COM27	COM43	COM134	COM150
1BH												COM28	COM44	COM133	COM149
1CH												COM29	COM45	COM132	COM148
88H												COM137	COM153	COM24	COM40
89H												COM138	COM154	COM23	COM39
8AH												COM139	COM155	COM22	COM38
8BH												COM140	COM156	COM21	COM37
8CH												COM141	COM157	COM20	COM36
8DH												COM142	COM158	COM19	COM35
8EH												COM143	COM159	COM18	COM34
8FH												COM144	COM160	COM17	COM33
90H												COM145	COM1	COM16	COM32
91H												COM146	COM2	COM15	COM31
92H												COM147	COM3	COM14	COM30
93H												COM148	COM4	COM13	COM29
94H												COM149	COM5	COM12	COM28
95H												COM150	COM6	COM11	COM27
96H												COM151	COM7	COM10	COM26
97H												COM152	COM8	COM9	COM25
98H												COM153	COM9	COM8	COM24
99H												COM154	COM10	COM7	COM23
9AH												COM155	COM11	COM6	COM22
9BH												COM156	COM12	COM5	COM21
9CH												COM157	COM13	COM4	COM20
9DH												COM158	COM14	COM3	COM19
9EH												COM159	COM15	COM2	COM18
9FH												COM160	COM16	COM1	COM17


MX	0	SEG1	SEG2	SEG3	SEG4	SEG5			SEG380	SEG381	SEG382	SEG383	SEG384
	1	SEG382	SEG383	SEG384	SEG379	SEG380			SEG5	SEG6	SEG1	SEG2	SEG3

Example for memory mapping: let MX = 0, MY = 0, SL = 0, LC[7:6] = 10b (RRRRR-GGGGG-BBBBB, 64K-color), according to the data shown in the above table (R: 11111b, G: 11111b, B: 11111b):

⇒ 1st Byte write data: 11111111b

⇒ 2nd Byte write data: 11111111b

12. Inspection Standards/检验标准

Item	Criterion for defects	Defect type
1) Display on inspection/显示效果	(1) Non display (2) Vertical line is deficient (3) Horizontal line is deficient (4) Cross line is deficient	Major
2) Black / White spot/黑点或白点	Size Φ (mm) Acceptable number $\Phi \leq 0.3$ Ignore (note) $0.3 < \Phi \leq 0.45$ 3 $0.45 < \Phi \leq 0.6$ 1 $0.6 < \Phi$ 0	Minor
3) Black / White line/黑线或白线	Length (mm) Width (mm) Acceptable number $L \leq 10$ $W \leq 0.03$ Ignore $5.0 \leq L \leq 10$ $0.03 < W \leq 0.04$ 3 $5.0 \leq L \leq 10$ $0.04 < W \leq 0.05$ 2 $1.0 \leq L \leq 10$ $0.05 < W \leq 0.06$ 2 $1.0 \leq L \leq 10$ $0.06 < W \leq 0.08$ 1 $L \leq 10$ $0.08 < W$ follows 2) point defect Defects separate with each other at an interval of more than 20mm	Minor
4) Display pattern/显示模式	 $\frac{A+B \leq 0.28}{2}$ $0 < C$ $\frac{D+E \leq 0.25}{2}$ $\frac{F+G \leq 0.25}{2}$ Note: 1) Up to 3 damages acceptable 2) Not allowed if there are two or more pinholes every three-fourth inch.	Minor
5) Spot-like contrast irregularity/均匀度	Size Φ (mm) Acceptable Number $\Phi \leq 0.7$ Ignore (note) $0.7 < \Phi \leq 1.0$ 3 $1.0 < \Phi \leq 1.5$ 1 $1.5 < \Phi$ 0 Note: 1) Conformed to limit samples. 2) Intervals of defects are more than 30mm.	Minor
6) Bubbles in polarizer/玻璃内有气泡	Size Φ (mm) Acceptable Number $\Phi \leq 0.4$ Ignore (note) $0.4 < \Phi \leq 0.65$ 2 $0.65 < \Phi \leq 1.2$ 1 $1.2 < \Phi$ 0	Minor
7) Scratches and dent on the polarizer/玻璃刮痕/凹痕	Scratches and dent on the polarizer shall be in the accordance with "2) Black/white spot", and "3) Black/White line".	Minor
8) Stains on the surface of LCD panel/玻璃上有污点	Stains which cannot be removed even when wiped lightly with a soft cloth or similar cleaning.	Minor
9) Rainbow color/杂色	No rainbow color is allowed in the optimum contrast on state within the active area.	Minor
10) Viewing-area encroachment/玻璃边线出现在视域	Polarizer edge or line is visible in the opening viewing area due to polarizer shortness or sealing line.	Minor
11) Bezel appearance/铁筐外观	Rust and deep damages that are visible in the bezel are rejected.	Minor
12) Defect of land surface 表面缺陷	Evident crevices that are visible are rejected.	Minor
13) Parts mounting/部件安装	(1) Failure to mount parts (2) Parts not in the specifications are mounted (3) For example: Polarity is reversed, HSC or TCP falls off.	Minor
14) Part alignment/部件结合度	(1) LSI, IC lead width is more than 50% beyond pad outline. (2) More than 50% of LSI, IC leads is off the pad outline.	Minor
15) Conductive foreign matter (solder ball, solder hips)/杂质 (焊接遗留物)	(1) $0.45 < \Phi$, $N \geq 1$ (2) $0.3 < \Phi \leq 0.45$, $N \geq 1$, Φ : Average diameter of solder ball (unit: mm) (3) $0.5 < L$, $N \geq 1$, L : Average length of solder chip (unit: mm)	Minor
16) Bezel flaw/铁筐缺陷	Bezel claw missing or not bent	Minor
17) Indication on name plate (sampling indication label)/标志	(1) Failure to stamp or label error, or not legible.(all acceptable if legible) (2) The separation is more than 1/3 for indication discoloration, in which the characters can be checked.	Minor

12. Handling precautions 注意事项

1. Refrain from strong mechanical shock and forces to the module. It may cause improper operating or damage to the module.
防止震动和压迫模组，以免造成模组损坏和运行正常。
2. The polarizer used on the display surface is easily scratched and damaged. Extreme care should be taken when handling. When cleaning the display surface, use soft cloth with a solvent recommended : ethyl alcohol , isopropyl or hexane) and wipe gently, do not use the following solvents : water, ketone or aromatics .
模组表面的偏光极易被刮伤和损坏，所以操作是要非常小心。请用蘸有乙醇等溶剂的湿软布轻轻擦拭，不要使用水，乙酮等溶剂。
3. Wipe off water or oil drop immediately If you leave drop for a long time, stain and discoloration may occur.
要立即擦拭掉屏幕上的油滴和水滴，否则会出现污点和杂质。
4. Do not touch pads or pins of interface directly with bare hands. When handling the LCD module, put on a soft glover like finger-glover.
不要直接用手去触碰接口处的金属管脚。当操作模组的时候，请配带软指套。
5. Protect the module from static electricity, it may cause damage to CMOS LSI.
模组需要有防静电保护，否则会损坏CMOS LSI。
6. To prevent LCD panels from degradation, do not operate or store them exposed directly to sunlight or high temperature/humidity.
不要直接在太阳,高温或潮湿环境下操作和储存LCD模组，以免影响模组的质量。
7. If the liquid crystal leaks from the panel it should be kept away from the eyes and mouths. In case of contact with skins, wash away thoroughly with soap and water.
若有液晶漏出，务必避免其入眼入口。若沾到皮肤上了，马上用肥皂和水冲洗干净。
8. Soldering should be only performed on the I/O terminals within the temperature of $280 \pm 20^{\circ}\text{C}$ and soldering time should be less than 4 seconds.
要在 $280 \pm 20^{\circ}\text{C}$ 的条件下在I/O终端实现焊接，并且保证焊接时间短于4秒。
9. Supply voltage within the specified voltage limit, the maximum rating, higher voltage cause the shorter LCD life or damaged.
绝对要在指定的电压范围内驱动模组， 因为如果在高于指定电压的情况下驱动模组，会使模组寿命变短
10. Do not input any signals before power is turned on. Do not connect or disconnect the module on the state of Power-ON.
供电之前不要输入任何信号，不要在通电时连接和段开 LCD 模组。