



No.	Pin Name	Terminal
1	VSS	
2	VDD	
3	NC	
4	A0	
5	NC	
6	NC	
7	SCLK	
8	DATA	
9	/RES	
10	NC	
11	NC	
12	NC	
13	NC	
14	NC	
15	/CS	
16	NC	
17	NC	
18	NC	
19	BLK	
20	BLA	

- Specifications:
- 1) LCD Display Type : STN-Y/G,Positive,
  - 2) Polarizer : Transmissive
  - 3) Viewing Direction : 6 °CLDCK
  - 4) Drive Method : 1/64Duty; 1/9Bias
  - 5) Operating Voltage : VDD=3.3V or 5.0V
  - 6) Operating Temperature : -10°C~60°C
  - 7) Storage Temperature : -20°C~70°C
  - 8) Controller/Driver IC : ST7565
  - 9) Backlight : Yellow or Green LED, 20mA~35mA

Customers Approval With Signature And Chop  
Approved By \_\_\_\_\_ Date \_\_\_\_\_

Backlight Circuit  
BLK  
BLA

**科飞研科技**

Dwg Title: **COG12864TM093A** REV 00

Scale	Unit	Tol.	Dwg No.	Date
	mm	±0.2	05312015	

Drawn	Checked	Approved	Date
LMX			2012-05-31

